VG921m

19" LCD MONITOR
WITH CLEARMOTIV™
8MS VIDEO RESPONSE

The business for business

The 19" ViewSonic VG921m LCD monitor combines multimedia versality with a new elegant, slim design. Thanks to the ClearMotiv™ 8ms video response time, images appear with pinpoint focus and superior clarity when viewing moving images. Premium contrast ratio and brightness levels deliver superb picture quality with vivid, brillant colours. And with the integrated 3-watt sound system you can enjoy a true multimedia experience, delivering rich stereo sound to your desktop. The fully featured VG921m is an ideal LCD monitor for home, small/home office, corporate, government or education use.

It's not just a multimedia LCD. It's a ViewSonic.

8MS RESPONSE FOR MULTIMEDIA EXCELLENCE

> ClearMotiv™ 8ms video response time
Ultra-fast 8ms video response delivers broadcast-quality full motion video.

> Dynamic Structure™ technology
Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.

> Multimedia enhanced
Save workspace and enjoy rich stereo sound with built-in stereo speakers.

> Ultra-high 700:1 contrast ratio (typ.) and 300cd/m² brightness (typ.) and for rich, detailed images

> OnView® controls for superior screen adjustability
Screen adjustments are precisely made via an easy-to-use on-screen menu.

> VESA® 100mm wall mount interface and Kensington® security port

> 1280 x 1024 resolution

> PC and Mac® compatible

> TCO'03 and ENERGY STAR® qualified

MORE THAN 2000 AWARDS

VIEWSONIC
PRODUCTS, PROGRAMS, AND SERVICES

ViewSonic
the choice of professionals

ViewSonic
the choice of professionals

VG921m

19" LCD MONITOR WITH CLEARMOTIV™ 8MS VIDEO RESPONSE

LCD	Type	19" TN colour TFT active matrix SXGA LCD
	Display Area	37.6cm horizontal x 30.1cm vertical; 48.3cm diagonal
	Pixel Pitch	0.294mm
	Optimum Resolution	1280 x 1024@60Hz
	Pixel Clock	135MHz
	Contrast Ratio	700:1 (typ.)
	Viewing Angle	150° horizontal, 135° vertical (at 10:1) 160° horizontal, 155° vertical (at 5:1)
	Response Time	8ms (off-on-off) (typ.)
	Colour Support	16.2M colours (6-bit+2-bit FRC)
	Light Source	Long life, 50000 hrs. (min.)
	Brightness	300cd/m^2
	Panel Surface	Anti-glare (3H)
VIDEO INPUT	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohm) Frequency Fh: 30–82kHz, Fv: 56–76Hz
	Synchronisation	H/V separate (TTL)
COMPATIBILITY	PC	VGA up to 1280 x 1024 non-interlaced
	Mac®[1]	Power Mac™ up to 1280 x 1024 non-interlaced
CONNECTOR	Analogue	15-pin mini D-Sub (detachable cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin AC plug (CEE22)
AUDIO	Speakers	2 x 1.5 watt integrated stereo speakers
POWER	Voltage	AC 100–240V, 50/60Hz (auto switch), internal power supply
	Consumption	39 watt (typ.), <1 watt in power save mode
ERGONOMICS	Tilt	Down 5°, Up 20° (90° for wall mount)
CONTROLS	Basic	Power, menu [1], up, down, select [2], mute
	OSD	Auto image adjust, contrast, brightness, input select (D-sub, audio (volume, mute), ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
OPERATING CONDITONS	Temperature	5°C–35°C
	Humidity	20%–80% (non-condensation)
DIMENSIONS	(W x H x D mm)	426 x 457 x 205 (physical with stand) 426 x 397 x 64 (physical without stand) 497 x 512 x 158 (packaging)
WEIGHT	Net	5.2kg (with stand) 4.3kg (without stand)
	Gross	6.8kg (with stand)
REGULATIONS		TCO'03, TÜV/GS, TÜV/Ergo, ISO13406-2 (pixel failure class II), CE, CB, GOST-R, PSB, ENERGY STAR ,YCO03, UL/cUL, FCC-B, ICES 003, NOM, Argentina-TÜV/S, SASO, BSMI, C-Tick, MIC, CCC, WEEE, RoHS
POWER MANAGEMENT		Meets TCO'03 and ENERGY STAR® standards
SECURITY		Kensington® security port
WALL MOUNT		VESA FDMI 100mm x 100mm
PACKAGE CONTENT		LCD Monitor, power cable, D-sub video cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

TCO Development TCO'03 DISPLAYS www.tcodevelopment.com

RoHS COMPLIANT™

ISO 9001 FM 40187

ISO 14001 EMS 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK

ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux	Tel: +32 (0)56 85 26 27
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)9 5406 4070
ViewSonic Italy	Tel: +39 02 73 95 50 22
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Netherlands	Tel: +31 (0)20 491 9254
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

[1] May require optional Mac adapter.

Copyright © 2006, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VG921m 10/06-UK